



MPS Hybrid Inverter

Product Features:

Safe & Reliable

- Built-in isolation transformer for high load adaptability;
- Perfect protection function for inverter and battery;
- Redundancy design for important functions;

Abundant Configuration

- Integrated design, easy to integrate;
- Support simultaneous access of load, battery, power grid, diesel and PV;
- Built-in maintenance bypass switch, improve system availability;

Intelligent & Efficient

- Support battery capacity and discharge time prediction;
- Smooth switching between on and off grid, uninterrupted supply of load;
- Operate with EMS to monitor system status in real time;

Friendly & Flexible

- Various working modes can be set flexibly;
- PV controller modular design, easy to expand;





Technical Specification	MPS0030	MPS0050	MPS0100	MPS0150	MPS0250	MPS0500
-------------------------	---------	---------	---------	---------	---------	---------

AC(On-Grid)

Max Output Power(kVA)	33	55	110	165	275	550
Rated Power(kW)	30	50	100	150	250	500
Rated Voltage(V)	400					
Rated Current (A)	43	72	144	216	361	722
Voltage Range(V)	320~460					
Rated Frequency (Hz)	50/60					
Frequency Range(Hz)	45~55/55~65					
THDi	<3%					
Power Factor	1lagging~1leading					
AC Connection	3W+N+PE					
Transformer Ratio	100/400	200/400	270/400	270/400	270/400	315/400

AC(Off Grid)

Max Output Power(kVA)	33	55	110	165	275	550
Rated Power(kW)	30	50	100	150	250	500
Rated Voltage(V)	400					
Rated Current(A)	43	72	144	216	361	722
THDu	≤1% Linear; or ≤5% Nonlinear					
Rated Frequency(Hz)	50/60					
Overload Capacity	110% Long-Term					

Photovoltaic Input

Max.PV Input Voltage(V)	1,000					
Max.PV Power(kW)	60/120	60/120	120/180/240	120/180/240	300/360	600/660/720
MPPT Voltage Range(V)	250-850					
MPPT Full load Voltage Range(V)	450-850					

Battery

Battery Voltage Range(V)	250~850	320~850	420~850	420~850	420~850	500~850
Max. Charging Power(kW)	60/120	60/120	120/180/240	120/180/240	300/360	600/660/720

General Data

Dimension W*D*H(mm)	800*800*1,900	800*800*1,900	1,200*800*2,050	1,200*800*2,050	(600*720*2,050)*1+ 1,200*800*2,050	(600*720*2,050)*2+ 1,600*1050*2,050
Weight(kg)	620/650	720/750	1,120/1,150/1,180	1,250/1,280/1,310	1,980/2,010	3,265/3,295/3,325
Operation Temperature	-30°C ~ 55°C					
Relative Humidity	0 ~95% Non-Condensing					
Ingress Protection	IP20					
Noise Emission(dB)	<70dB					
Altitude	5,000m(>3,000 Derating)					
Cooling	Air Cooling					

Display And Communication

Display	LCD Touch-Screen					
BMS Communication	RS485, CAN					
EMS Communication	RS485, TCP/IP					

Certificates

EN62109-1/-2, EN62477-1, EN61000-6-2, EN61000-6-4, South Africa NRS097-2-1:2017, Pakistan & India IEC61727, IEC62116, IEC 61683